

- 01. interior trims
- 02. equipment
- 03. engines
- 04. equipment and options

# 01. interior trims



techno



techno esprit Alpine and iconic esprit Alpine

### 02. equipment

#### techno

#### design

- 19" 'streamline' diamond cut alloy wheels
- · brushed satin chrome Renault logo
- · shark fin antenna
- · auto-tilting & folding wing mirrors with puddle lamp
- · tinted rear windows and tailgate
- · flush electric door handles

#### on-board features

- ingenious® rear armrest [rear storage, 2x usb-c ports, cup holders + smartphone / tablet holder]
- wireless phone charger
- · 12.3" driver information display
- · 12" openR link touchscreen with built in Google Automotive services [incl. Navigation], Arkamys audio [6-speakers], with DAB & Bluetooth
- · frameless auto-dimming rear view mirror with light & rain sensor
- heated recycled heather grey fabric / titanium black grained coated textile / yellow stitching with driver's seat having electric lumbar function

- · MULTI-SENSE with 4 driving modes and up to 48 ambient lighting colours
- heated steering wheel in grained bio sourced and recycled textile
- electric tailgate
- high central console with sliding armrest and 2 USB sockets
- dual-zone automatic climate control
- · hands-free keycard heat pump
- wireless smartphone mirroring compatible with Android Auto™ and Apple CarPlay™
- electrically adjustable, automatically foldable demisting door mirrors
- $\boldsymbol{\cdot}$  biosourced and recycled textile dashboard
- digital operating instructions in the vehicle's multimedia system

#### safety

- adaptive vision LED headlights with fog light function
- · rear view camera, with front, rear and side parking sensors
- contextual adaptive cruise control
- · blind spot warning

#### electric

- · electric journey programming with Google Maps\*
- presetting of battery temperature when driving (prior to DC rapid charging)
- regenerative braking (five levels with One Pedal driving) adjustable via a paddle shifter on the steering wheel
- up to 11kW AC charging and up to 150 kW DC
- · V2L capabilites available (requires accessory adaptor)

#### techno esprit Alpine (techno+)

#### design

- · 20" 'speedway' diamond cut alloy wheels
- · esprit Alpine badaina
- · matte black roof bars
- $\cdot$  front and rear bumper pieces and satin grey door protectors
- brushed ice black renault logo
- $\cdot\,$  glossy black window and quarter panel trim

#### on-board features

- · sports seats with embossed titanium black recycled mesh / recycled quilted arain coated textile / blue stitching
- blue carpet
- esprit Alpine interior
- soft fabric dashboard
- $\cdot\,$  electric front seats with massage function for driver
- face ID: auto selects driver profile and seat position

#### options

 two-tone paint, including optional exclusive matte shadow arev

### iconic esprit Alpine (techno esprit Alpine+)

#### on-board features

- · Harman Kardon® 9-speaker high-fidelity audio system
- · Solarbay® opacifying panoramic sunroof

#### safety

- · smart rear view mirror
- · 360° around view 3D camera
- · handsfree parking

two-tone paint, including optional exclusive matte shadow grey

\* included for 5 years.

Android Auto™ is a trademark of Google Inc. Apple CarPlay™ is a trademark of Apple Inc. Google, Google Assistant, Google Play and Google Maps are trademarks of Google LLC.

## 03. engines

mox torque EEC-Nm         280         300           bottery         secondary (kWh)         60         87           technology         likhium-ion         likhium-ion           total number of modules/cells         400         400         400           better) weight (kg)         405         515         515           heat pump         yes         yes         yes           bridirectional chargering         daptive langle-or three-phase         adaptive		EV60 170hp comfort range	EV87 220 hp long range
renge and consumption         430         610           certified of riving range in WLTP cycle (killometres)***         430         610           certified of riving range in WLTP cycle (killometres)***         19"         171           wheel size of certified version***         19"         19"           electric engine teachnology         synchronous with colled rotor         synchronous with colled rotor           mox. torque EEC-Nm         280         37           teactre engine teachnology         816 hours         18 hours           took copocity (kWh)         60         87           tock londogy         180 hours         120 hours           total voltage (V)         400         120 hours           total voltage (V)         405         15 lithium-ion           total voltage (V)         405         15 lithium-ion           biddrection dharger**         405         15 lithium-ion           biddrection dharger**         40 yes         40 yes           biddrection dh	useful battery capacity (kWh)	60	87
certified driving range in WLTP cycle (klilometres) <sup>61</sup> 430         610           certified consumption in combined cycle (kWh/km)         10°         171           wheel size of certified version of certified versions of wheel size of certified versions of the certified version of the certified versi	number of seats	5	5
destricted consumption in combined cycle (kWh/km)         19"         17.1           wheel alize of certified version <sup>10</sup> 19"         19"           electric engine technology         synohronous with colled root	range and consumption		
whele size of certified version <sup>®</sup> 19°           engine           electric engine technology         synchronous with colled rotor         synchronous	certified driving range in WLTP cycle (klilometres) <sup>(1)</sup>	430	610
electrice engine technology         synohronous with coiled rote         synohronous with coiled rote         synohronous with coiled rote         control of the control of	certified consumption in combined cycle (kWh/km)		17.1
Selectric engine technology	wheel size of certified version <sup>(2)</sup>	19"	19"
max. torque EEC-Nm         280         300           bottery         cusable capocity (kWh)         60         87           technology         lithium-ion         lithium-ion           total voltage (V)         400         400           total unbare of modules / cells         212/192           bottage (Mg)         405         515           beat pump         yes         yes           6-directional chargeria         daptive single-or three-phase         daptive single-or three-phase         daptive single-or three-phase           6-directional chargeria         daptive single-or three-phase         daptiv	engine		
battery         sectors of the composity (kWh)         60         87           technology         (Birbium-ion)         (Birbium-ion)           technology         400         400           total voltage (V)         400         400           total voltage (V)         405         156           battery weight (kg)         405         515           bettery pump         yes         yes           bi-directional chargerin         adaptive single-or there-phase         daptive-inter-phase           bi-directional chargerin         adaptive single-or three-phase         daptive-inter-phase           bi-directional chargerin         aptive-inter-phase         photolitic single-phase inter-phase           bi-directional chargerin         30hrs 30         46 hrs 19           bi-directional chargerin         30hrs 30         46 hrs 19           14 We terminal chargering phase in Al (0-100%)         30hrs 30         9 hrs           14 We terminal chargering phase in Al (100%)         10 hrs 30	electric engine technology	synchronous with coiled rotor	synchronous with coiled rotor
usable capacity (kWh)         60         87           technology         İlthium-ion         İlthium-ion           total voltage (V)         400         400           total number of modules / cells         12/192           battery weight (kg)         405         515           better weight (kg)         405         515           better pweight (kg)         405         515           bridge tional charger <sup>19</sup> adaptive single- or three-phase         deptive single- or three-phase           CP (kW)         up to 11         up to 11         up to 11           CP (kW)         up to 180         46 hrs 19         44 hrs	max. torque EEC-Nm	280	300
technology         İlithium-ion         İlithium-ion         İlithium-ion           total valorage (V)         400         400           total number of modules / cells         12/92           battery weight (kg)         405         515           beattery weight (kg)         yes         yes           bridirection loharger <sup>10</sup> daptive single-orthere-phase         aptive single-orthere-phase           Bridirection loharger <sup>10</sup> qupto 11         up to 11         up to 11         up to 150 ct peak           Briding time <sup>10</sup> 100         yes 10         100 ct ye	battery		
total voltage (V)         400         400           total number of modules / cells         12/19/2           bacture y weight (kg)         405         515           heat pump         yes         yes           bi-directional charger®         daptive single- or three-phose         register of three-phose           Series AC (kW)         up to 180 at peak         up to 180 at peak           DC (kW)         up to 180 at peak         up to 180 at peak           23 kW domestic socket (single-phase 10 A) (0-100%)         30hrs30         4 hrs19           7.4kW domestic socket (single-phase 10 A) (0-100%)         30hrs30         9 hrs           1 kW terminal (three-phase 16 A) (0-100%)         30hrs30         9 hrs           20 Crapid charge (15-80%)         3 at most 30         9 hrs           9earbox         3 at most 30         9 hrs           9earbox (type         at to most 10 gearbox)         at to most 10 gearbox)           9earbox (type         3 at to most 10 gearbox)         at to most 10 gearbox)           1 performance         1         1         1           1 performance         1         1         1         1         1         1         1         1         1         1         1         1         1         1 <td>usable capacity (kWh)</td> <td>60</td> <td>87</td>	usable capacity (kWh)	60	87
total number of modules / cells         12/192           battery weight (kg)         405         515           heat pump         9se         yes           bif-directional charger <sup>in</sup> adaptive single- or three-phase         3daptive single- or three-phase           Cerick (kW)         up to 11         up to 11         up to 11           Cerick (kW)         up to 15 or tpeak         up to 15 or tpeak         up to 15 or tpeak           Charging time**         23 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           24 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           14 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           24 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           14 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           24 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           14 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           24 kW domestic socket (single-phase) (A) (0-100%)         30 hrs 30         4 hrs 19           25 kW domestic socket (single-phase) (30 kW domestic socket (single-phase) (30 kW domestic socket (single-phase) (30 kW domestic socket (single-phase) (30 kW d	technology	lithium-ion	lithium-ion
battery weight (kg)         405         515           heat pump         yes         yes           bi-directional charger***         adaptive single- or three-phase         adaptive single- or three-phase         deaptive single- or three-phase           Series AC (kW)         up to 11         up to 11         up to 11           Ck (kW)         up to 150 at peak         up to 150 at peak           charging time***         up to 150 at peak         up to 150 at peak           2.3 kW domestic socket (single-phase 10 A) (0-100%)         30hrs30         46 hrs10           7.4 kW domestic charging point (32A single-phase) (0-100%)         9hrs40         12 hrs 56           11 kW terminal (three-phase 16 A) (0-100%)         30mrs30         46 hrs10           Oc rapid charge (15-80%)         32mins         37 min           gearbox         32mins         37 min           gearbox type         automatic (gearbox)         automatic (gearbox)           number of froward gears         1         1         1           performace         1         1         1           to speed (mph)         150 - 87kWh - 170         105         1           0-100km (s)         7.9         7.9         7.9           steering         yes (electric)         yes (el	total voltage (V)	400	400
bi-directional charger <sup>19</sup> dadaptive single- of three-phase         ded pittine charger in the phase         ded pittine charger in the phase in the	total number of modules / cells		12/192
bi-directional charger <sup>(n)</sup> adaptive single- or three-phase         displies of three-phase           Series AC (kW)         up to 11         up to 11           CC (kW)         up to 150 at peak         up to 150 at peak           CD (kW)         up to 150 at peak         up to 150 at peak           Charging time <sup>(n)</sup> 30hrs30         46 hrs 19           7.4kW domestic socket (single-phase) (0-100%)         9hrs40         12 hrs 56           1kW terminal (three-phase 16 A) (0-100%)         6hrs30         9 hrs           DC rapid aborge (15-80%)         32mins         37min           gearbox         1         1           gearbox type         automatic (gearbox)         automatic (gearbox)           gearbox type         1         1           gearformance         1         1           tops peed (mph)         150-87kWh-170         105           0-100km kg         7.9         7.9           2 steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           turning circle between kerbs (m)         10.92         10.92           turning circle between kerbs (m)         10.92         10.92           turning circle between kerbs (m)	battery weight (kg)	405	515
Series AC (kW)         up to 110         up to 110         up to 150 at peak           DC (kW)         up to 150 at peak         up to 150 at peak           charging time**/         up to 150 at peak         up to 150 at peak           2.3 kW domestic socket (single-phase) (0-100%)         30hrs30         46 hrs 19           7.4kW domestic charging point (32A single-phase) (0-100%)         9hrs40         12 hrs 56           1kW terminal (three-phase 16 A) (0-100%)         32mins         37 min           DC rapid charge (15-80%)         32mins         37 min           gearbox         32mins         37 min           gearbox type         automatic (gearbox)         automatic (gearbox)           umber of forward gears         1         1           performance         1         1         1           performance <t< td=""><td>heat pump</td><td>yes</td><td>yes</td></t<>	heat pump	yes	yes
DC (kW)         up to 150 at peak         up to 150 at peak           chorging time™         23 kW domestic socket (single-phase 10 A) (0-100%)         30hrs30         46 hrs 19           24 kW domestic charging point (32A single-phase) (0-100%)         9hrs40         12 hrs 56           1kW terminal (three-phase 16 A) (0-100%)         6hrs30         9 hrs           DC rapid charge (15-80%)         32mins         37 min           gearbox         9earbox         30montic (gearbox)         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1         1           performance         1         1         1           top speed (mph)         150-87kWh-170         105         0           -100kmh (s)         79         79         79           steering         yes (electric)         yes (electric)         yes (electric)         yes (electric)         10-2         10-92	bi-directional charger <sup>(3)</sup>	adaptive single- or three-phase	adaptive single- or three-phase
charging time(**)           2.3 kW domestic socket (single-phase 10 A) (0-100%)         30 hrs30         46 hrs 19           7.4kW domestic socket (single-phase) (0-100%)         9 hrs40         12 hrs 56           1kW terminal (three-phase 16 A) (0-100%)         6 hrs30         9 hrs           DC rapid charge (15-80%)         32 mins         37 min           gearbox           gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         79         79           steering           power steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           weels and tyres         10.92         10.92           standard wheel rims (")         10" (techno), 20" (techno esprit Alpine), 10" (techno), 20" (techno esprit Alpine)         10 cionic esprit Alpine)           10" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H	Series AC (kW)	up to 11	up to 11
2.3 kW domestic socket (single-phase 10 A) (0-100%)         30hrs30         46hrs19           7.4kW domestic charging point (32A single-phase) (0-100%)         9hrs40         12 hrs 56           11 kW terminal (three-phase 16 A) (0-100%)         6hrs30         9 hrs           DC rapid charge (15-80%)         32mins         37 min           gearbox         utomatic (gearbox)         automatic (gearbox)           pearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance           to speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering           power steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres           standard wheel rims (")         19" (techno.),20" (techno.esprit Alpine),1" (techno.),20" (techno.esprit Alpine)         10.00(e.esprit Alpine)           10" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55	DC (kW)	up to 150 at peak	up to 150 at peak
7.4kW domestic charging point (32A single-phase) (0-100%)         9hrs40         12 hrs 56           11 kW terminal (three-phase 16 A) (0-100%)         6hrs30         9 hrs           DC rapid charge (15-80%)         32 mins         37 min           gearbox         gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance           top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.54         2.34	charging time <sup>(3)</sup>		
11 kW terminal (three-phase 16 A) (0-100%)         6hrs30         9 hrs           DC rapid charge (15-80%)         32 mins         37 min           gearbox         gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance         Top speed (mph)         150-87kWh-170         105           0-100kmh (s)         7.9         7.9           steering         yes (electric)         yes (electric)           power steering         yes (electric)         yes (electric)           urning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         3         19" (techno), 20" (techno esprit Alpine), 19" (techno), 20" (techno esprit Alpine)         10 cionic esprit Alpine)           19" Michelin e-primacy tyre dimensions         2.05/55 Ri9 97 H         2.05/55 Ri9 97 H         2.05/55 Ri9 97 H           20" Michelin e-primacy tyre dimensions         2.35/45 R20 100 H         2.35/45 R20 100 H         2.35/45 R20 100 H           braking         FR DISK 350x30+ Caliper D45*2         RDISK 330x16+Caliper D45*2         RDISK 330x16+Caliper D45*2	2.3 kW domestic socket (single-phase 10 A) (0-100%)	30hrs30	46 hrs 19
DC rapid charge (15-80%)         32 mins         37 min           gearbox         gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance         top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         steering           power steering of steering - wheel turns         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         1°" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           1°" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 R1 H         205/55 R19 R1 H         205/55 R19 R1 H         205/55 R19 R1 H         205/55 R19 R1 H         20	7.4kW domestic charging point (32A single-phase) (0-100%)	9hrs40	12 hrs 56
gearbox         gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance         top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         yes (electric)         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         19" (techno), 20" (techno esprit Alpine)         10.92         10.92           10.92         number of steering-wheel turns         2.34         2.34           2.34         2.34         2.34           2.99" Micheline-primacy tyre dimensions         205/55 R19 97 H	11 kW terminal (three-phase 16 A) (0-100%)	6hrs30	9 hrs
gearbox type         automatic (gearbox)         automatic (gearbox)           number of forward gears         1         1           performance         top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         bower steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         19" (techno), 20" (techno esprit Alpine), 19" (techno esprit Alpine)         10.92           10.92         yes (electric)         yes (electric)           10.92         10.92           10.92         10.92           10.92         10.92           10.92         10.92           10.92         yes (electric)           10.92         10.92           10.92         10.92           10.92         10.92           10.92 <t< td=""><td>DC rapid charge (15-80%)</td><td>32mins</td><td>37 min</td></t<>	DC rapid charge (15-80%)	32mins	37 min
number of forward gears         1         1           performance         top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         3         3         3           standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)         10.92         2.04 <td>gearbox</td> <td></td> <td></td>	gearbox		
performance           top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering           power steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)         10.00 (techno esprit Alpine)	gearbox type	automatic (gearbox)	automatic (gearbox)
top speed (mph)         150 - 87kWh - 170         105           0-100kmh (s)         7.9         7.9           steering         yes (electric)         yes (electric)           power steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           19" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H         235/45 R20 100 H           braking         FR DISK 350x30+ Caliper D45*2         FR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePKB         RR DISK 330x16+ Caliper D48 ePK	number of forward gears	1	1
teering         yes (electric)         yes (electric)           power steering         yes (electric)         yes (electric)           turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         *****         ************************************	performance		
steering         yes (electric)         yes (electric)           power steering         yes (electric)         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres         standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           19" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           braking         Front: ventilated disc Ø (mm)         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D48 ePK           weight (kg)         empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	top speed (mph)	150 - 87kWh - 170	105
Dower steering   Yes (electric)   Yes (electric)	0-100kmh (s)	7.9	7.9
turning circle between kerbs (m)         10.92         10.92           number of steering-wheel turns         2.34         2.34           wheels and tyres	steering		
number of steering-wheel turns         2.34         2.34           wheels and tyres         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           19" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           braking         FR DISK 350x30+ Caliper D45*2	power steering	yes (electric)	yes (electric)
wheels and tyres         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           19" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           braking         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2           rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DISK 330x16+Caliper D48 ePKB           weight (kg)         empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	turning circle between kerbs (m)	10.92	10.92
standard wheel rims (")         19" (techno), 20" (techno esprit Alpine, 19" (techno), 20" (techno esprit Alpine)           19" Michelin e-primacy tyre dimensions         205/55 R19 97 H         205/55 R19 97 H           20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           braking         front: ventilated disc Ø (mm)         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2           rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DIS	number of steering-wheel turns	2.34	2.34
19" Michelin e-primacy tyre dimensions   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   205/55 R19 97 H   20" Michelin e-primacy tyre dimensions   235/45 R20 100 H   235/45 R20 10	wheels and tyres		
20" Michelin e-primacy tyre dimensions         235/45 R20 100 H         235/45 R20 100 H           braking         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2           front: ventilated disc Ø (mm)         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2           rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DISK 330x16+Caliper D48 eP           weight (kg)         empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	standard wheel rims (")		
braking         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*3           rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DISK 330x16+Caliper D48 ePKB           weight (kg)         empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	19" Michelin e-primacy tyre dimensions	205/55 R19 97 H	205/55 R19 97 H
Front: ventilated disc Ø (mm)         FR DISK 350x30+ Caliper D45*2         FR DISK 350x30+ Caliper D45*2           rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DISK 330x16+Caliper D48 ePKB           weight (kg)         empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	20" Michelin e-primacy tyre dimensions	235/45 R20 100 H	235/45 R20 100 H
rear: drum (T), cooled disc (CD)         RR DISK 330x16+Caliper D48 ePKB         RR DISK 330x16+Caliper D48 ePKB           weight (kg)           empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	braking		
weight (kg)           empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	front: ventilated disc Ø (mm)	FR DISK 350x30+ Caliper D45*2	FR DISK 350x30+ Caliper D45*2
empty weight in running order (min/max)         1746/1817         1,840/1,916           gross train weight (GTW)         3,440         3,541           gross vehicle weight rating (GVWR)         2,340         2,441	rear: drum (T), cooled disc (CD)	RR DISK 330x16+Caliper D48 ePKB	RR DISK 330x16+Caliper D48 ePKB
gross train weight (GTW) 3,440 3,541 gross vehicle weight rating (GVWR) 2,340 2,441	weight (kg)		
gross train weight (GTW) 3,440 3,541 gross vehicle weight rating (GVWR) 2,340 2,441	empty weight in running order (min/max)	1746/1817	1,840/1,916
		3,440	3,541
payload (min/max.) 523/594 525/601	gross vehicle weight rating (GVWR)	2,340	2,441
22901	payload (min./max.)	523/594	525/601
max. braked trailer weight 1,100 1,100			1,100


AC: alternating current. DC: direct current
(1) Based on techno long range. WLTP figures shown for comparability purposes only. Actual real world driving results may vary depending on factors including the starting charge of the battery, accessories fitted after registration, weather conditions, driving styles and vehicle load. (2) the size of the wheel rims may affect the vehicle's driving range. (3) maximum power and charging times are based on optimal charging conditions for the vehicle and for the charging point (peak power). The maximum power accepted by the battery (mainly in DC charging) varies depending on the battery's state of charge and the exterior temperature. Range communicated in WLTP cycle.

# 04. equipment and options

	techno	techno esprit Alpine	iconic esprit Alpine
technology & entertainment			
wireless smartphone replication with Apple CarPlay™ & Android Auto™	•	•	•
wireless phone charger	•	•	•
12" openR link touchscreen with built in Google Automotive Serivices [incl. Navigation], Arkamys audio [6-speakers], with DAB & Bluetooth <sup>(1)(2)</sup>	•	•	-
12" openR link touchscreen with built in Google Automotive Services [incl. Navigation], 9-speaker Harman Kardon audio system, DAB & Bluetooth <sup>(1)(2)</sup>	-	-	•
voice control for navigation system: Google assistant built in		•	•
bluetooth		•	•
12.3" driver information display	•	•	•
USB-C ports: 2 front & 2 rear		•	•
multifunctional steering wheel			•
convenience			
adaptive cruise control with speed limiter	•	•	•
active driver assist: adaptive cruise control + lane centring	•	•	•
active driver assist: intelligent contextual adaptive cruise control + lane centring		•	•
intelligent speed assist: traffic sign recognition with speed alert		•	
blind spot recognition & rear detection with emergency lane keeping assist		•	•
rear cross traffic alert with rear active emergency braking system		•	•
emergency lane keep assist including solid line, oncoming traffic & road edge			
detection [includes: lane keeping assist, lane departure warning & lane change warning]	•	•	•
emergency brake assist			•
safe stopping distance warning	•	•	•
multi collision braking	•	•	•
occupant safe exit & child locking function for rear doors & windows		•	•
my safety switch: shortcut to personalise configuration of driving aids		•	•
e-call: automatic emergency assist		•	•
"QRescue"; QR code fireman access for technical information		•	
hill start assist		•	•
front, rear & side parking sensors		•	•
handsfree parking			•
rear view camera		•	•
360 around view 3D camera		-	•
frameless auto-dimming rear view mirror with light & rain sensor		•	-
smart rear view mirror	-		•
MULTI-SENSE: driving modes and up to 48 ambient lighting colours		•	•
face ID: auto selects driver profile and seat position		•	•
Eco mode function	•	•	•
paddle shift levers for regenerative braking with one pedal driving	-	-	-
vehicle sound for pedestrians	•		
interior features	<del>-</del>	<del>-</del>	
2-zone automatic climate control with humidity sensor & air recycling		-	
recycled heather grey fabric / titanium black grained coated textile / yellow stitching	<u> </u>	<u> </u>	<u>-</u>
embossed titanium black recycled mesh / recycled quilted grain coated textile / blue stitching	-	•	•
esprit Alpine interior [blue stitching, blue interior of storage compartments, blue inserts in door panel, sporty seats]	-		•
soft fabric dashboard	•		
manual front seats with height adjustment and driver's electric lumbar function	-	<u>-</u>	<u>-</u>
front electric seats [6 way] with 2 way lumbar and massage function on driver seat	-	<u> </u>	<u>-</u>
		<u> </u>	<u>-</u>
heated front seats			
heated steering wheel	<u> </u>	<u> </u>	<u> </u>
manual height & reach adjustable steering wheel	•	•	•
electric front windows: one touch & anti pinch function	•	•	•
electric rear windows: one touch & anti pinch function	•	•	•
front interior 12V power outlet	•	•	•
high central console with sliding armrest & storage ingenious armrest [rear storage, 2x usb-c ports, cup holders + smartphone / tablet	•	•	•
holder]			
2nd row - 3 seat bench with 40/20/40 split	•	•	•
rear headrests x3	•	•	•
black carpet	•	-	-
blue carpet	-	•	•
luggage compartment light	•	•	-

# 04. equipment and options

	techno	techno esprit Alpine	iconic esprit Alpine
exterior features			
19" 'streamline' diamond cut alloy wheels	•	•	-
20" speedway diamond cut alloy wheels	-	•	•
full LED headlights with adaptive LED front & rear fog lights (afs)	•	•	•
auto low/high beam	•	•	•
front fog lights	•	ī	•
LED daytime running lights	•		
2 reversing lights	•		•
moirage front & rear signature lighting with dynamic turn signal	•		•
automatic headlights & windscreen wipers with rain sensors	•	•	•
auto-tilting & folding wing mirrors with puddle lamp	•	•	•
wing mirrors [black]	•	•	•
esprit Alpine styling [esprit Alpine badging]	-	•	•
tinted rear windows & tailgate	•	•	•
heated rear window			•
Solarbay opacifying panoramic sunroof			
shark fin antenna			
electric power boot opening	•	•	•
metallic paint: one tone	0	0	0
metallic paint: two tone	-	0	0
safety		<u> </u>	<u> </u>
active emergency braking system - urban, pedestrian/cyclist & junction function	•	•	•
anti-lock brake system (abs)		•	•
driver attention alert	-		<u> </u>
driver & passenger front airbag	<u> </u>	<u> </u>	-
side airbags	<u> </u>	<u> </u>	-
passenger airbag deactivation	<u> </u>	<u>-</u>	<u>-</u>
ISOFIX child seat fixing points on rear outermost seats	-		-
adjustable driver & front passenger safety seat belts	<del></del>	<u> </u>	
driver, front passenger and 3 rear passengers seatbelt reminder (SBR)		<u> </u>	<u> </u>
seatbelt pretensioners - front	<u> </u>	<u> </u>	<u> </u>
•	-	<u> </u>	-
seatbelt pretensioners - rear for 3 seats	-	<u> </u>	-
3x3 point rear seat belts	-	-	-
electric parking brake with autohold	<u> </u>	<u> </u>	<u> </u>
super locking electronic stability program (esp)	<u> </u>	<u> </u>	<u> </u>
	-	<u> </u>	-
tyre inflation kit	•	•	•
tyre pressure warning light	•	•	•
security			
hands-free keycard with keyless entry	•	•	•
immobiliser	•	•	•
remote central locking	•	•	•
engine start button	•		•
locking wheel nuts	•	•	•
electric car features			
heat pump	•	•	•
battery pre-conditioning for DC charging	•	•	•
5m mode 3 charging cable	•	•	•
AC11 charging with up to DC150	•	•	•
bi-directional charge: power to object [V2L]	•	•	•
bi-directional charge adaptor [V2L]	0	0	0
SD pyro switch; disconnect the battery from high-voltage network to ensure safety as needed	•		•



Every precaution has been taken to ensure that the contents of these technical specifications were accurate and up to date at the time of release. This document was created using pre-production models and prototypes. In line with its policy of continuous product improvement, Renault reserves the right to modify the specifications, vehicles and accessories described and featured at any time. Any such modifications are communicated to Renault dealers as quickly as possible. Depending on the country of sale, certain versions may differ and certain equipment may be unavailable (as standard, as an option or as an accessory). Please contact your nearest dealer for the latest information. For technical printing reasons, the colours featured in this document may differ slightly from those of the actual paintwork or interior trim. All rights reserved. Reproduction in any format and by any means of all or part of these specifications is prohibited without prior written authorisation from Renault.